



Fig. Deposit safe AM25, hinge right
E-Lock M-Locks EM3520, without equipment, drop-in equipment LBE150 front and center



Burglary protection
according to safe type



according to safe type



4102 (light fire protection)



Domestic insurable
according to safe type



Commercial insurable
according to safe type

[Drop-in equipment LBE150]

Construction	massive steel structure with security blocking system
Weight	appr. 28 kg
Position	front, back, back protruding or upon request
Colour	inside and outside RAL 7037 dusty grey (always ident with safe colour) option: special colour according to RAL
Lock	cylinder lock with 5 keys option: further keys upon request
Drop-in goods	flexible envelopes max. DIN A4, max. 15 mm thick or cassettes with max. size 240 x 180 x 60 mm
Accessories	option: zipp-bag, cassette



Fig. Zipp-bag

[Deposit safes – drop in safes]

Safes with drop-in equipment offer a simple and secure depositing of e.g. daily cash receipts and are mainly used if more than one person deposit values (e.g. petrol stations, fast food and convenience stores).

- Drop-in goods (e.g. zipp-bag) are deposited through the drop-in flap into the safe.
- A security anti-fishing device prevents the later removal of a deposited bag.
- The deposited bags can only be removed by the manager of the safe.

[Product information]

All Wertheim safes can be equipped with a drop-in mechanism. According to the requested insurance class and the capacity of bags, the right safe can be chosen. Please note, that deposit safes are certified according to security class VSÖ—all other certification expired due to the opening of the drop-in mechanism. VDMA-safes with drop-in mechanism are delivered without certification label.

[Example deposit safe AM25RE]

Security class	burglary protection according to EN1143-1, VSÖ: Class EN 1
Hinge	DIN right – model designation R option: DIN left
Door opening angle	180°
Body	double-walled, filled with high resistant barrier material
Door structure	triple-walled, filled with high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
Locking mechanism	three-way moving boltwork with large steel bolts, protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Anchoring	prepared for floor and rear wall anchoring anchoring bolts and shields are supplied option: additional anchoring holes (customer specifies position)
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system
Colour	inside and outside RAL 7037 dusty grey option: special colour according to RAL
Lock	model designation E – electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary locks)
Equipment	it is recommended to install no internal equipment in deposit safes
Accessories	option: certified steel plinth to raise the level of the safe, fire protection door rebate seals, alarm switch set, interior lighting
Drop-in position	front and center option: on the back, on the back protruding, other options upon request
Maximum volume	subject to bag filling, position of drop-in equipment etc.