



-  EN1143-1
Burglary protection
-  EN15659
Fire protection (option)
-  VdS
Grade III
-  ECB-S
Grade III
+ LFS60P (option)
-  ISO
Class EN 3
-  a2p
Class III E
-  DIN
4102 (light fire protection)
-  Domestic insurable
up to EUR 200.000
-  Commercial insurable
up to EUR 100.000

Fig. Safe CWS1901, hinge left
E-Lock La Gard Combogard PRO, 4 shelves

Model	Outside dimensions			Inside dimensions		SH	Volume	Weight
	h x w x d (mm)			h x w x d (mm)			(l)	(appr. kg)
CWS0849RK / CWS0849RE	848 x	645 x	565	695 x	495 x 320	1	110	625
CWS0850RK / CWS0850RE	848 x	810 x	725	695 x	660 x 480	1	220	865
CWS1000RK / CWS1000RE	1003 x	810 x	725	850 x	660 x 480	2	269	1010
CWS1200RK / CWS1200RE	1193 x	810 x	725	1040 x	660 x 480	2	329	1110
CWS1600RK / CWS1600RE	1538 x	810 x	725	1385 x	660 x 480	3	439	1365
CWS1901RK / CWS1901RE	1883 x	810 x	725	1730 x	660 x 480	4	548	1640
CWS1903RK / CWS1903RE	1883 x	1110 x	725	1730 x	960 x 480	4	797	2030
CWS1902K / CWS1902E	1883 x	1110 x	725	1730 x	960 x 480	4	797	2070
CWS1904K / CWS1904E	1883 x	1415 x	725	1730 x	1265 x 480	4	1050	2480

SH = Shelf

Please add 60 mm to the listed outside depth for mountings.

[Safes]

[Type CWS]

A distinctive feature of the CWS series safes is their solid construction plus their size (CWS 1902 and CWS1904 double-doored) and they are available with optional fire protection – tested and certified in grade LFS60P. Safes weighing less than 1.000 kg must be anchored.

[Product information]

- Hinge DIN right – model designation R (CWS1902, CWS1904 double-doored)
option: DIN left
- Door opening angle 180°
- Body double-walled, reinforced, filled with armoured, high resistant barrier material
- Door structure triple-walled, reinforced, filled with armoured, high resistant barrier material,
internal boltwork protected by sheets of hardened steel
to give extra anti-drill resistance
- Locking mechanism three-way moving boltwork with large steel bolts,
protected by glass plate with additional emergency re-lockers,
fix engaging steel bolts on the hinge side
- Anchoring fitted for floor anchoring
anchoring bolts and shields are supplied for CWS0849, CWS0850
option: additional anchoring holes (customer specifies position)
- Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system
- Colour outside RAL 7035 light grey + RAL 7045 tele grey1, inside RAL 7035 light grey
option: special colour according to RAL
- Lock model designation K – double-bit lock VdS class 2, S+G, 1 key guide tube, 2 bits
model designation E – electronic lock VdS class 2, M-Locks EM3520
option: other lock models (primary lock or possible secondary locks)
- Equipment shelf adjustable (height setting 69 mm, CWS0849 60 mm)
option: additional shelf, inside locker
option (from CWS0850 up): drawer, pull-out shelf
- Accessories option: fire protection door rebate seals, alarm switch set, interior lighting
- Option additional certified fire protection LFS60P – except models:
CWS0849, CWS1902, CWS1904
bolted version (without fire protection) – assembly on site

[Equipment options]

