



- EN1143-1
Burglary protection
- VdS
Grade III
- ECB-S
Grade III
- EN 3**
Class EN 3
- Class III E**
(except K-Lock Secu)
- DIN 4102** (light fire protection)
- Domestic insurable
up to EUR 200.000
- Commercial insurable
up to EUR 100.000

Fig. Swing-in door safe CWP0901, hinge right
K-Lock Secu 2 keys (125 mm), 1 lockable drawer, 2 pull-out shelves

[Cashier equipment Inkiess 880PL]

Cashier equipment consists of coin trays, coin and note boxes, full details upon request.



Fig. Cashier equipment Inkiess 880PL

Model	Outside dimensions	Inside dimensions	Volume	Weight
	h x w x d (mm)	h x w x d (mm)	(l)	(appr. kg)
CWP0651RK / CWP0651RE	648 x 850 x 754	486 x 514 x 590	147	515
CWP0901RK / CWP0901RE	878 x 850 x 754	716 x 514 x 590	217	635
CWP0652K / CWP0652E	648 x 1308 x 754	486 x 820 x 590	235	730
CWP0902K / CWP0902E	878 x 1308 x 754	716 x 820 x 590	346	890

Please add 20 mm to the listed outside depth for mountings.

[Swing-in door safes – desk safes]

[Type CWP]

CWP series safes are fitted with swing-in doors and make working with the door open easy. The dimensions are chosen to enable an installation under a desk making it ideal for use in small areas.

[Product information]

- Hinge** DIN right – model designation R (CWP0652, CWP0902 double-doored)
- Door opening** swing-in doors – upon opening, the doors slide into the side of the safe, leaving the area in front of the safe completely free – several safes can be positioned next to each other in a row, without open doors interfering each other
- Body** triple-walled, reinforced, filled with armoured, high resistant barrier material
- Door structure** triple-walled, reinforced, filled with armoured, high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
- Locking mechanism** three-way moving boltwork with large steel bolts protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
- Anchoring** fitted for floor anchoring
anchoring bolts and shields are supplied
option: additional anchoring holes (customer specifies position)
- Alarm connection** VdS-certified cable channels to allow connection to a burglar alarm system
- Colour** inside and outside RAL 7035 light grey
option: special colour according to RAL
- Lock** model designation K – double-bit lock VdS class 2, Secu 2 keys (125 mm)
model designation E – electronic lock VdS class 2, M-locks EM3520
option: other lock models (primary lock or possible secondary lock)
- Equipment** option: lockable drawer, pull-out shelf, cashier equipment Inkiess
lowest pull-out shelf with automatic push-out (100 mm)
- Accessories** option: alarm switch set, interior lighting
- Option** electronic drawer control,
version multisafe certified in accordance with VdS 2450 grade III (SE105301)

[Electronic drawer control]

Fig. keypad input unit



Swing-in door safes, equipped with electronic controlled drawers, take today's requests of modern bank organisation into account. Different access entitlements to the safe facilities can be organized and changed any time in a very simple way.

The operation of the drawers as well as programming the opening codes is possible via keypad input unit with a 4-digit code on an easy to read display. The keypad is built in even into the desktop.

- Unlocking a drawer by input of a 4-digit, programmable opening code
- Individual drawers have facility of time delayed opening
- Adjustable drawer activation time
- Attack alarm activation which allows the drawer opening by input of the attack/duress alarm